



GPR-2500

% Oxygen Transmitter - GP or Certified for Hazardous Gas / Area use

<b>Product Parent Code: GPR-2500</b> <b>General Purpose or Hazardous Area certified Industrial % Oxygen Transmitter</b> <b>2 wire loop powered Transmitter provides a 4-20mA output with temperature compensation</b> <b>4 measurement ranges 0-1, 0-5, 0-10 to 0-25%; manual or auto-ranging measurement ranges</b> <b>delrin sensor housing; stainless steel pipe-work and 1/8" tube fittings; wall mount fiberglass NEMA 4X enclosure.</b>		
<b>Product Ordering Code {Feature A}+{Feature B}+{Feature C}+{Feature D}+{Feature M}</b>		
<b>Feature</b>	<b>Item</b>	<b>Description</b>
<b>Feature {A}</b>	<b>Base Model</b>	
	GPR-2500	Oxygen Transmitter (%)
<b>Feature {B}</b>	<b>Hazardous Configuration</b>	
	B1	General Purpose
	B2	cMETus, ATEX, IECEx, UKEX - I.S. barrier supplied loose
<b>Feature {C}</b>	<b>Sample System</b>	
	C0	No sample system required
	C1	A-4442 Coalescing filter (fitted on inlet)
	C2	Sample panel fitted (see separate part number)
<b>Feature {D}</b>	<b>Sensor</b>	
	D1	GPR-11-32-4
	D2	XLT-11-24-4 (CO2 & acidic background gases)
<b>Feature {M}</b>	<b>Certificates (Only add if required)</b>	
	* M2	NIST Calibration Cert
<b>* On certain labor intensive services, no discount can be offered. These items are always offered at list price.</b>		

Ordering Examples

<b>GPR-2500+B1+C0+D1</b>	<b>Oxygen Analyzer (PPM), Wall mount enclosure, no sample system, GPR-11-60-4 sensor</b>
--------------------------	--

<b>Order Code</b>	<b>Description</b>
<b>Replacement Sensors</b>	
GPR-11-60-4	% replacement sensor
XLT-11-24-4	% replacement sensor - CO2 & acidic background gases
<b>Spares</b>	
BARR-1002	Intrinsically Safe Barrier - Replacement (B2 Option only)
A-4442-4	Coalescing Filter Assembly



## GPR-2500 A

### % Oxygen Analyzer - Industrial

<b>Product Parent Code: GPR-2500A</b> <b>General Purpose Industrial % Oxygen Analyzer</b> <b>4 measurement ranges: 0-1%, 0-5%, 0-10% to 0-25% O2; manual or auto-ranging measurement ranges</b> <b>2 user configurable alarm contacts; 4-20mA signal output; modbus communications</b> <b>delrin sensor housing; stainless steel pipe-work with 1/8" tube fittings; wall mount fiberglass NEMA 4X enclosure; requires 12-28V DC power.</b>		
<b>Product Ordering Code {Feature A}+{Feature B}+{Feature C}+{Feature D}+{Feature F}+{Feature M}</b>		
Feature	Item	Description
Feature {A}	<b>Base Model</b>	
	GPR-2500A	Oxygen Analyzer %
Feature {B}	<b>Power</b>	
	B1	12-28VDC
Feature {C}	<b>Sample System</b>	
	C0	No sample system required
	C1	A-4442 Coalescing filter (fitted on inlet)
	C2	Sample panel fitted (see separate part number)
Feature {D}	<b>Sensor</b>	
	D1	GPR-11-60-4
	D2	XLT-11-24-4 (CO2 & acidic background gases)
Feature {M}	<b>Certificates (Only add if required)</b>	
	* M2	NIST Calibration Cert
<b>* On certain labor intensive services, no discount can be offered. These items are always offered at list price.</b>		

### Ordering Examples

<b>GPR-2500A+B1+C0+D1</b>	<b>Oxygen Analyzer (PPM), Wall mount enclosure, 12-28VDC power, no sample system, GPR-11-60-4 sensor</b>
---------------------------	--

Order Code	Description
<b>Replacement Sensors</b>	
GPR-11-60-4	% replacement sensor
XLT-11-24-4	% replacement sensor - CO2 & acidic background gases
<b>Consumable items</b>	
FLTR-1037	Element for Coalescing Filter
<b>Spares</b>	
A-4442-4	Coalescing Filter Assembly

Please note: Analytical Industries Inc. adopts a continuous development program which sometimes necessitates specification changes without notice.  
Please contact us for the latest version. Issue No: GPR-2500/A\_V5