



TP9-BL

Temperature-controlled pyroelectric detector for laser power measurement from nW to 0.5 mW.



PRODUCT FAMILY KEY FEATURES

SPECTRALLY FLAT RESPONSE

These radiometers were developed for NIST, to be used with a broadband spectrometer to act as a spectral transfer standard when calibrating other detectors in the 0.25 to 15 μm range.

TEMPERATURE CONTROLLED POWER MEASUREMENT

Each head is composed of a low noise detector, thermistor, TE cooler and heatsink to compensate for any temperature change

THE ULTIMATE CHOICE IN MEASUREMENT STABILITY

Temperature control down to 0.05°C from 20 to 30°C gives a temperature coefficient <0.01 %, thus a voltage output stable to 0.01 %

2 SIZES AVAILABLE

- TP5-BL: 5 mm \varnothing pyroelectric sensor with organic black coating
- TP9-BL: 9 mm \varnothing pyroelectric sensor with organic black coating

TO BE USED WITH THE STEP-CONTROLLER

Plug your TP sensor into the STEP-Controller for power supply and temperature control. You can then use the analog output with a scope or lock-in

COMPATIBLE STAND

[STAND-D-233](#)



SPECIFICATIONS

MEASUREMENT CAPABILITIES

Maximum average power (continuous)	500 μW
Noise equivalent power ¹	5 nW
Spectral range ²	0.25 - 15 μm
Typical rise time	0.2 s
Power calibration uncertainty	± 2.5 %
Chopper frequency ³	10 Hz, 50% duty cycle
Temperature stability	$\pm 0.05^\circ\text{C}$
Voltage response stability	$\pm 0.01\%$

1. With STEP-Controller and scope. Noise is < 11 nW RMS with STEP-controller and Lock-In.
2. NIST-traceable calibration at 632.8 nm.
3. SDC-500 digital optical chopper sold separately

DAMAGE THRESHOLDS

Maximum average power density	50 mW/cm ²
-------------------------------	-----------------------

PHYSICAL CHARACTERISTICS

Aperture diameter	9 mm
Absorber	BL
Dimensions	50.8 \varnothing X 48.3D mm
Weight	0.227 kg

ORDERING INFORMATION

TP9-BL

Specifications are subject to change without notice. Refer to the user manual for complete specifications.



INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us